



BF20 (20hp Outboard)

The BF20 delivers unrivalled innovation to the portable range. It's a powerful, efficient and clean operator!

INTRODUCTION

RELIABILITY IN A COMPACT DESIGN

With a high output 350cc displacement and long-stroke design, the BF20 is a top performer, providing optimum torque at any speed.

Programmed Ignition (PGM-IG) also accurately controls ignition timing during start-up and across the entire rev range for optimum overall operation. A 12amp (electric start) alternator also ensures excellent charging power to keep batteries in top condition.

Thanks to its incredibly lightweight design, the BF20 is also very easy to transport. A foldaway handle positioned at the exact balance point of the engine makes it easy to carry in a level position.

SUPERIOR HANDLING POWER

The BF20 is equipped with Power Tilt and Gas Assist Tilt variations - perfect for effortless engine tilt operations and shallow-water running.

Cruising is improved and more comfortable with Honda's unique pendulum-motion mounting system. This system is specially designed to reduce vibration and maximise user comfort.

A convenient Forward Mount Shift Lever allows fingertip shifting, while a Twist Grip Throttle and Tensioner ensures superior throttle friction, minimising driver fatigue.

FOUR-STROKE ENGINE DESIGN

Honda's world-renowned engineering combines proven reliability and superior fuel efficiency, with no oil mixing, resulting in a healthier experience for you and the environment.

And while conventional two-circuit carburettors go directly from a lean mixture at idle to a rich setting at full throttle, the BF20 adds a third, middle stage for better economy and smoother, stronger operation.

The BF20 also features an integrated warning system, designed to protect the engine from severe damage due to low oil, over-revving or overheating.

LONG-LASTING PERFORMANCE

A crankshaft-driven, automotive-style trochoid oil pump ensures the long-term durability of critical engine components.

Honda's patented 'double sealed' multi-layered paint process means that the BF20 is also protected from corrosion. Sacrificial anodes and stainless steel technology, along with waterproof connectors, all work together so you get the most out of your engine.

And with an industry leading 7 Year Warranty and 100 dealers located around Australia, no matter where your Honda BF20 takes you, you'll go there with peace of mind.

REVERSE EXHAUST RELIEF

Additional exhaust relief above the cavitation plate allows the prop to run in clean, exhaust-free water producing more thrust.

EASY ONE HAND STARTING

Working together, a built-in decompression release and Digital CDI system set the ignition timing during start-up. Just 60% of the normal effort is required to pull-start the engine by hand!

AUTO START ENRICHMENT

On electric-start models, the engine automatically adjusts the air/fuel mixture for quick, easy starting and warm-up operation

FRESH WATER FLUSHPORT

Flushes debris and saltwater out of the engine, extending the life of the outboard.

LONGER TILLER HANDLE

The BF20 has a convenient longer tiller handle for increased control and reduced steering effort. The extended handle is made of a new lightweight composite for increased durability and weight reduction.

UP FRONT TILLER CONTROLS

The convenient Forward Mount Shift Lever allows fingertip shifting. Twist Grip Throttle and Tensioner allows for superior throttle friction control, minimising driver fatigue.

EZ STEER FRICTION CONTROL

Unique lever design allows operator to precisely adjust steering tension for improved control and comfort.

SPECS

ENGINE

TYPE 4-stroke SOHC 2-cylinders / 4-valves

DISPLACEMENT 350cc

BORE & STROKE 59 x 64 mm

FULL THROTTLE RPM RANGE 5,000-6,000 RPM

RATED POWER 20HP @ 5,500 RPM

COOLING SYSTEM Water Cooled

INDUCTION 1 carburetor

IGNITION SYSTEM PGM-IG

STARTING SYSTEM Recoil/Electric

EXHAUST Through prop

ALTERNATOR 12-Amp (electric) / 6-Amp (manual)

POWER TRIM & TILT Power tilt

GAS-ASSISTED TILT Available

TRIM RANGE	4-stage 8 - 12 - 16 - 20
-------------------	--------------------------

TILT RANGE	72
-------------------	----

SAFETY FEATURES

EMERGENCY STOP SWITCH	Standard
------------------------------	----------

OIL PRESSURE ALERT	Standard
---------------------------	----------

TEMPERATURE ALERT	Standard
--------------------------	----------

REV-LIMITER	Standard
--------------------	----------

SPEEDOMETER PICKUP	n/a
---------------------------	-----

DRIVE

GEAR RATIO	2.08:1
-------------------	--------

GEAR SHIFT	F-N-R
-------------------	-------

PROPELLER	4-blade aluminium
------------------	-------------------

DIAMETER X PITCH (S-TYPE)	9-1/4 x 10 inches
----------------------------------	-------------------

DIAMETER X PITCH (L-TYPE)	9-1/4 x 10 inches
----------------------------------	-------------------

DIAMETER X PITCH (X-TYPE)	9-1/4 x 10 inches
----------------------------------	-------------------

DIMENSIONS

OVERALL LENGTH	650mm
-----------------------	-------

OVERALL WIDTH	350mm
----------------------	-------

OVERALL HEIGHT (S-TYPE)	1,240mm
--------------------------------	---------

OVERALL HEIGHT (L-TYPE)	1,240mm
--------------------------------	---------

OVERALL HEIGHT (X-TYPE)	1,380mm
--------------------------------	---------

TRANSOM HEIGHT (S-TYPE)	433mm
--------------------------------	-------

TRANSOM HEIGHT (L-TYPE)	563mm
--------------------------------	-------

TRANSOM HEIGHT (X-TYPE)	703mm
--------------------------------	-------

DRY WEIGHTS (S-TYPE)	46.5kg
-----------------------------	--------

DRY WEIGHTS (L-TYPE)	46.5kg
-----------------------------	--------

DRY WEIGHTS (X-TYPE)	52kg
-----------------------------	------

VISIT HONDA MARINE WEBSITE

For terms and conditions please visit http://about.hondamc.com.au/Terms_and_Conditions

The information in this document is valid as of 08/05/2017. For the most up to date information please visit <http://marine.honda.com.au>